



Buyer acknowledges and agrees that: (i) these structural values are theoretical in their derivation and are not intended to be relied on by Buyer; (ii) a registered Structural Engineer should be employed by Buyer for the determination of the suitability of the material and assemblies for Buyer's specific use;

CUSTOMER'S SUPPLIED CAD FILE

UNMARKED RADII = RADIUS TO SUIT
 BREAK CORNERS = 0.100 (2.54) R.
 (z) = 0.218 (5.54) R. (4)

(*) = 0.010(0.25) R. X 0.010(0.25)D.

NO SURFACES EXPOSED.

ARCHITECTURAL FENCE & RAILINGS	UNSPECIFIED WALL THICKNESS	
	0.188(4.78) ±0.019(0.50)	
EST. AREA 3.586 in ² 2314 mm ²	OUT PER. 19.626 IN 498 MM	
EST. WT. 4.304 LBS/FT. 6.405 KG/M	FACTOR 9	
EST. PER. 37.950 IN 964 MM	C.C.D. 6.885 IN 175 MM	
DWN BY B.V.	ALLOY 6061-T6	SCALE 1:1 DATE 01-06-01

BREAK ALL CORNERS .016"R (0.41 mm)R UNLESS OTHERWISE NOTED.

STANDARD ALUMINUM ASSOCIATION TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED